



# STAINLESS STEEL CONTINUOUS HINGES

## CONCEALED LEAF


Hager heavy duty steel continuous hinges offer proven reliability that can stand to the daily rigors of high traffic, high impact areas. The hinges are designed and engineered to evenly distribute door weight along the full length of the door, which eliminates localized stress of the door frame. The following hinges are for door 1-3/4" (44mm) thick and up to 600 pounds.



**790-900**




**790-905**




**790-907**

- Flush Mount



**790-911**

- Swing Clear




**790-915**




## HALF MORTISE

For retrofit applications and for square edge doors only



**790-904**



**790-906**




---

# STAINLESS STEEL CONTINUOUS HINGES

## HALF SURFACE

For security moldings

US32D



790-903




---

## FULL SURFACE

For ADA upgrade work

US32D



790-909



---

### NOTES

- 14 gauge Type 304 stainless steel
- 1/4" (6.4 mm) diameter stainless steel pin
- Dual 6/6 Nylon bearings between each knuckle
- Dutch door, hospital tips, custom hole patterns, and special finishes are available on stainless steel continuous hinges

### Electrical Hinge Modifications - check website for model availability

- Exposed Electric Switch (EIS)
- Electric Power Transfer Preparation (EPT)
- Concealed Electric Through-Wire (ETW)